

Notified Body No. 2812

## Certificate of Constancy of Performance

### 2812-CPR-AC0010

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

## H107, H202, H203 Grade 13 Stainless Steel Lift-Off Hinges See Annex A

**Intended use: For use on fire/smoke compartmentation doors, and escape route doors**

Essential characteristics	Performance	Harmonised technical specification
<b>Mechanical test evidence: 529PCT, WIL 407856, WIL 433042 WIL 129696, WIL 420365 &amp; WIL 535759 Fire Test Evidence: WF 136052 &amp; WF 138907 Iss 11</b>		
Self-closing Initial friction torque (door mass 120kg) Static load Load deformation  Overload  Shear strength  Hinges for use on fire-resistant and/or smoke-controls doors	< 4Nm  Passed with a displacement under load: - lateral < 2mm - vertical < 4mm and a residual displacement after unloading: - lateral < 0.6mm - vertical < 0.3mm - within the shaded area of figure G.1  Passed  Not applicable to lift-off hinges  Grade 1: suitable for use on fire/smoke resistant door assemblies	<b>EN 1935:2002 / AC:2003</b>
Durability  Families of hinges with common design features  Corrosion resistance	Passed a 200,000 cycle test with a maximum wear: - lateral < 0.5mm - vertical < 1mm and with a maximum frictional torque. - after 20 cycles < 4Nm - after the completion of 200,000 cycles < 4Nm  The hinge covered by this certificate is the hinge tested  Grade 4: 240 hours	
Dangerous substances	Pass: the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Notified Body No. 2812

## Certificate of Constancy of Performance

### 2812-CPR-AC0010

Placed on the market under the name of:

**Royde & Tucker Limited  
Bilton Road  
Cadwell Lane  
Hitchin  
Hertfordshire  
SG4 0SB  
United Kingdom**

and produced in the manufacturing plant:

**CQB28702-1**

**This is coded format, and the information is held by the Notified Body.**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard:

**EN 1935:2002 / AC:2003**

Under System 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **11/12/2020** and re-issued on **11/11/2024** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **23/07/2025**

ERO Project Reference: **034621 P1700**



**Pascal Coget  
General Manager - European Certification**

CSF408-NL 8.0

## Certificate of Constancy of Performance

### 2812-CPR-AC0010

#### Annex A

Model Reference	Description
H107-RR-BSS H107-RS-BSS H107-LR-BSS H107-LS-BSS	110 x 98 x 3.2mm stainless steel concealed bearing lift-off hinge Satin brushed stainless steel Right & left handed. Radiused or square corners
H202-RR-BSS H202-RS-BSS H202-LR-BSS H202-LS-BSS	102 x 89 x 3.3mm stainless steel concealed bearing lift-off hinge Satin brushed stainless steel Right & left handed. Radiused or square corners
H203-RR-BSS H203-RS-BSS H203-LR-BSS H203-LS-BSS	102 x 102 x 3.3mm stainless steel concealed bearing lift-off hinge Satin brushed stainless steel Right & left handed. Radiused or square corners With or without dog bolt

<b>316B</b>	<b>SS316 stainless steel hinges available in the following finishes:</b> Satin brushed stainless steel	<b>316P</b>	<b>Polished stainless steel</b>
<b>BSS</b>	<b>SS304 stainless steel hinges available in the following finishes:</b> Satin brushed stainless steel	<b>PSS</b>	<b>Polished stainless steel</b>
<b>ABR</b>	Antique brass	<b>RBZ</b>	RT bronze
<b>ABZ</b>	Antique bronze	<b>SBB</b>	Simulated brushed brass
<b>BLK</b>	Black powder coated	<b>SBL</b>	Simulated brass, lacquered
<b>BNP</b>	Bright nickel plated	<b>SNP</b>	Satin nickel plated
<b>DBZ</b>	Dark bronze	<b>SPB</b>	Simulated polished brass
<b>EBP</b>	Electro brass plated	<b>WHI</b>	White paint powder coat
<b>FMB</b>	Flat matt black powder coat	<b>XABR</b>	Antique brass variant
<b>IBU</b>	Imitation bronze	<b>XBNP</b>	Bright nickel plated variant
<b>NST</b>	Non-standard painted	<b>XDBZ</b>	Dark bronze variant
<b>NSTP</b>	Non-standard plated	<b>XIBU</b>	Imitation bronze variant
<b>OBZ</b>	Old bronze	<b>XOBZ</b>	Old bronze variant
<b>PBL</b>	Polished brass plated, lacquered	<b>XRZB</b>	RT bronze variant
<b>PBZ</b>	Polished bronze	<b>XSNP</b>	Satin nickel plated variant
<b>PNP</b>	Polished nickel plated	<b>XSPB</b>	Simulated polished brass variant
<b>PVD</b>	PVD brass		